



Motor Vehicle Act

MOTOR ASSISTED CYCLE REGULATION

B.C. Reg. 151/2002

Deposited and effective June 21, 2002

Last amended March 22, 2018 by B.C. Reg. 56/2018

Consolidated Regulations of British Columbia

This is an unofficial consolidation.

B.C. Reg. 151/2002 (Insurance Corporation of British Columbia), deposited and effective June 21, 2002, is made under the *Motor Vehicle Act*, R.S.B.C. 1996, c. 318, s. 182.1.

This is an unofficial consolidation provided for convenience only. This is not a copy prepared for the purposes of the *Evidence Act*.

This consolidation includes any amendments deposited and in force as of the currency date at the bottom of each page. See the end of this regulation for any amendments deposited but not in force as of the currency date. Any amendments deposited after the currency date are listed in the B.C. Regulations Bulletins. All amendments to this regulation are listed in the *Index of B.C. Regulations*. Regulations Bulletins and the Index are available online at www.bclaws.ca.

See the User Guide for more information about the *Consolidated Regulations of British Columbia*. The User Guide and the *Consolidated Regulations of British Columbia* are available online at www.bclaws.ca.

Prepared by:
Office of Legislative Counsel
Ministry of Attorney General
Victoria, B.C.

Motor Vehicle Act

MOTOR ASSISTED CYCLE REGULATION

B.C. Reg. 151/2002

Contents

- 1 Motors
- 2 Wheels
- 3 Motor shut-off requirement
- 4 Generators
- 5 Brake performance requirement
- 6 Drive system and equipment securement
- 7 Electrical terminals

Motors

- 1** The motors of a motor assisted cycle must
 - (a) be electric motors,
 - (b) have continuous power output ratings that in total do not exceed 500 watts, and
 - (c) not be capable of propelling the motor assisted cycle at a speed greater than 32 km/hr on level ground.

[en. B.C. Reg. 56/2018, s. 1.]

Wheels

- 2**
 - (1) The wheels of a motor assisted cycle must be 350 mm or more in diameter.
 - (2) A motor assisted cycle must not have more than 3 wheels in contact with the ground.

Motor shut-off requirement

- 3**
 - (1) A motor assisted cycle must be equipped with a mechanism, separate from the accelerator controller, that
 - (a) allows the driver to turn the motors on and off from a normal seated position while operating the motor assisted cycle, or
 - (b) prevents the motors from turning on or engaging before the motor assisted cycle attains a speed of 3 km/hr.
 - (2) The motors of a motor assisted cycle must turn off or disengage if
 - (a) the operator stops pedaling,
 - (b) an accelerator controller is released, or
 - (c) a brake is applied.

[am. B.C. Reg. 56/2018, s. 2.]

Generators

- 4** A motor assisted cycle must not be equipped with a generator, alternator or similar device powered by a combustion engine.

Brake performance requirement

- 5** (1) A motor assisted cycle must be equipped with brakes on all wheels or on each axle.
- (2) The braking system must be capable of bringing the motor assisted cycle, while being operated at a speed of 30 km/hr, to a full stop within 9 m from the point at which the brakes were applied.

Drive system and equipment securement

- 6** The motor drive systems and all energy storage devices of a motor assisted cycle must be secured to prevent movement in any direction relative to the motor assisted cycle while the motor assisted cycle is operating.
- [am. B.C. Reg. 56/2018, s. 3.]

Electrical terminals

- 7** All electrical terminals on a motor assisted cycle must be completely insulated or covered.